



FDA Class II  
Medical Device\*



# MORE ROOM TO ROAM

## COMING AUGUST 30, 2023...

When life is on the move, you need to **think BIG** – and that’s exactly what we did.

Pride Mobility proudly introduces the **PX4**, a groundbreaking mobility solution to help your customers **embark on unforgettable journeys**.

This innovative mobility scooter offers an incredible **500-pound weight capacity** and a top speed of up to **9.3 mph**. Mix in a remarkable **23.4-mile battery range**, and the PX4 becomes a premier conduit for those seeking outdoor adventure.

The PX4 is the first of its kind to utilize **Near-Field Communication (NFC) technology** for its ignition system. The NFC key fobs are unique to each unit and will allow the user to start the scooter by waving the fob near the receiver. It’s easy, **secure**, and enhances the user experience.

With **seat sizes that range from 18” to 22” wide**, the PX4 has plenty of room to breathe for any eager traveler. The water-resistant user interface, enhanced lighting package, memory foam seating and full suspension will also provide **unparalleled comfort** and convenience as they maneuver through parks and urban landscapes.

Your customers can join us in **thinking BIG** with the PX4. To learn more about this exceptional mobility scooter, visit us at [www.pridemobility.com](http://www.pridemobility.com).




NFC  
KEY FOB




WEIGHT  
CAPACITY



CRUISING  
SPEED



SUSPENSION



23.4 MILE  
RANGE



LEARN  
MORE



FDA Class II  
Medical Device



USA: 800-800-8586 • CANADA: 888-570-1113

[pridemobility.com](http://pridemobility.com) •

\* Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.  
K0899 Power Mobility Device not coded by DME PDAC. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. Payer coding, coverage, and bundling guidelines may apply.