

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy Elite 14

Document Information: INFINF3086/Rev B/May 2014

Class Of Use	A
Weight Capacity:	300 lbs. (136 kg)
Maximum Speed: ¹	Up to 4 mph (6.4 km/h)
Ground Clearance: ²	3 in. (7.6 cm) at battery tray 2.5 in. (6.4 cm) at back of foot platform 1.5 in. (3.8 cm) at anti-tip wheels
Turning Radius: ²	24 in. (61 cm) without front riggings
Overall Size: ^{2, 6}	Length: 35.5 in. (90.2 cm) without front riggings 42.5 in. (107.9 cm) with front riggings Width: 24.25 in. (61.6 cm)
Drive Wheels:	14 in. (35.6 cm), solid
Caster Wheels:	6 in. (15.2 cm) solid, rear-mounted
Anti- tip Wheels:	3 in. (7.6 cm) solid, front-mounted
Suspension:	Limited
Range: ^{1, 4}	Up to 9.8 miles (15.77 km)
Component Weights: ⁵	Base: 98.5 lbs. (44.7 kg) Standard Seat (High Back): 51.5 lbs. (23.4 kg) with controller Batteries: 37 lbs. (16.8 kg) each
Drivetrain:	Two motor, Front-wheel drive
Brakes:	"Intelligent Braking" electronic regenerative, disc park brake
Batteries: ³	Two 12-volt, NF-22
Battery Charger:	5-amp off-board
Maximum Allowable Incline:	6° (10.5%)
Maximum Angle Capacity:	9° (15.8 %)
Maximum Obstacle Climbing Ability:	2 in. (5 cm)

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 Series EN12184 standards. All specifications subject to change without notice.



