Quick Start Guide



myAerX.com

Place the Aer X into the Aer X bag, ensure the filter inlet is not covered and air can flow freely



Slide battery into battery compartment by opening cover located on the top of your Aer X.



The charging port is located just above the filter inlet. Your Aer X may be charged during use.



Figure B

Insert the power cord into the Aer X if not using battery power or when charging battery.

Connect cannula
to the oxygen port.
NOTE: the oxygen
port connects
magnetically,
this is for your
safety (figure A)



An extended beep indicates your device is powering on. Please wait until start up is complete before changing any settings.

Place the nasal cannula in a comfortable position, with the prongs inside your nostrils

Your Aer X will now be providing oxygen when you inhale

Press the blue Power button to begin oxygen flow (figure B)



QUICK TROUBLE SHOOTING TIPS

If the 3B™ AER X should shut down during start up or, the Yellow light is illuminated after start up;

- 1. Check to make sure the 3B AER X cannula is attached. USING A DIFFERENT CANNULA THAN THE CANNULA SHIPPED WITH YOUR 3B AER or HAVING NO CANNULA ATTACHED may cause the 3B AER X to shut down during startup.
- 2. Make sure that the battery is charged. A DEPLETED BATTERY will cause the 3B AER X to shut down during startup.
- 3. Power down your 3B AER X and repeat the startup process.

If the 3B AER X fails to start again;

- 4. Disconnect the battery and connect the power supply.
- 5. Repeat the startup process.

If the 3B™ AER X continues to fail to start up, please contact your equipment provider for assistance.

41273B_0220

MID-63/v1.0