

There is Power Mobility. And then there's

# POWERFUL MOBILITY



CityRider



There is Power Mobility. And then there's

# POWERFUL MOBILITY

## CityRider

The CityRider gives you a relaxing ride wherever you travel thanks to an all-round suspension system fitted as standard. Coupled with a well-upholstered captain's chair and an adjustable tiller, the CityRider lets you find the perfect position for driving in comfort.



MAX SPEED  
**6.0**  
MPH



LOAD CAPACITY  
**350**  
LBS



BATTERY  
**35 Ah**  
SLA



RANGE  
**17**  
MILES

Overall Length	46.4" / 118 cm
Overall Width	23.2" / 59 cm
Overall Height (at Maximum Tiller Height)	48.8" / 124 cm
Overall Height - at Minimum Tiller Height	48.8" / 124 cm
Legroom - Floorboard Length x Width	12" x 19"
Deck Height - Floorboard to Floor	5.5"
Ground Clearance	2.5" / 75 mm
Turning Radius	56.3"/143 cm
Folded Overall Length	NA
Folded Overall Width	NA
Folded Overall Height	NA
Weight with Std.	206.4lbs/93.8kg
Weight with Batteries	206.4lbs/93.8kg
Weight without Batteries	154 lbs/70kg

Seat Type	Captain seat
Seat - Width & Depth & Height	19" x 17" x 26"
Seat - Cushion Thickness	2.5"~ 3"
Seat Height - Cushion to Deck	18"
Seat Height - Cushion to Floor	20.5"
Tire Type	Air
Rim Type Rear	Aluminum
Rim Type Front	4"
OEM Spec Rear	
Outside Diameter Rear	300-4x2(10")
Tire Width Rear	3"
OEM Spec Front	
Outside Diameter Front	300-4x2(10")
Tire Width Front	3"

Battery Type & Power	35AH SLA Batteries
Brake System	Electromagnetic Brake
Climbing Angle - Maximum Recommended	8°
Charger Type	4A Off-Board
Charging Time	>8hr
Controller	PG70A
*Driving Range	17 miles / 27.3 km
Load Capacity	350 lbs / 160 kg
Motor & Drive Location	470W 5300RPM
*Speed - Maximum	6 MPH
Colors	Red, Black, Sunset Orange
Tiller Type	DELTA
Throttle Control Type	Wigwag
Anti-Tipper Wheels-Rear	Yes

(\*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.